Instruction Manual

HI 38023 Total Chlorine **Extended Range Test Kit**



www.hannainst.com

Dear Customer

Thank you for choosing a Hanna Product.

Please read the instruction sheet carefully before using the test kit. It will provide you with the necessary information for correct use of the kit. If you need additional information. do not hesitate to e-mail us at tech@hannainst.com.

Remove the chemical test kit from the packing material and examine it carefully to make sure that no damage has occurred during shipping. If there is any noticeable damage, notify your Dealer or the nearest Hanna office immediately.

Each kit is supplied with:

- Potassium Iodide Solution, 1 bottle with dropper (30 mL);
- Sulfamic Reagent, packets (100 pcs);
- Starch Indicator, 1 bottle with dropper (25 mL);

PRINTED IN ITALY

12/00

- Thiosulfate Reagent, 1 bottle (100 mL):
- 1 calibrated plastic vessel (50 mL);
- 1 syringe (1 mL) with tip;
- 1 plastic pipette (1 mL);
- 1 spoon.

Note: Any damaged or defective item must be returned in its original packing materials.

SPECIFICATIONS

Range	10 to 200 mg/L (ppm) as Chlorine		
Smallest Increment	10 mg/L as Chlorine		
Analysis Method	Drop count titration		
Sample Size	1 mL		
Number of Tests	100		
Case Dimensions	235x175x115 mm (9.2x6.9x4.5")		
Shipping Weight	547 g (19.3 oz.)		

SIGNIFICANCE AND USE

The chlorination of water supplies and polluted waters is used mainly to destroy or deactivate disease-producing microorganisms. It also serves to improve the quality of drinking waters, as chlorine reacts with ammonia, iron, managnese, sulfide and some organic substances.

Nevertheless high amounts of chlorine will produce adverse effects, like formation of compounds which are potentially carcinogenic (e.g. chloroform) or harmful to aquatic life (e.g. chloramines). Thus it is essential to control that the proper amount of chlorine has been added in order to fulfill the primary purpose of disinfecting and to minimize any adverse effect.

Note: ma/L is equivalent to ppm (parts per million).

CHEMICAL REACTION

An iodometric titration method is used. The water sample is treated with potassium iodide and strongly acidified with acid. The amount of iodine generated is equivalent to the chlorine in the sample; the concentration of iodine is calculated by titration with thiosulfate ions that reduce iodine back to iodide ions.

INSTRUCTIONS

READ THE ENTIRE INSTRUCTIONS BEFORE USING THE KIT

- 1- Fill the calibrated vessel with tap water up to the 50 mL mark (the residual chlorine in tap water will not affect the test).
- 2- Add 5 drops of Potassium Iodide Solution and swirl

50 mL







3- Add 1 packet of Sulfamic Reagent and use the spoon to mix and dissolve









Note: To measure exactly 1.0 mL of sample

> with the syringe, push the plunger completely into the syringe and insert the tip into sample. Pull the plunger out until the lower edge of the seal is on the 0.0 mL mark of the syringe. Insert the syringe into the vessel and push the sample out until the lower edge of the seal is on the 1.0 mL mark.

5- Add 4 drops of Starch Indicator and swirl gently to mix. If chlorine is present, the solution will turn a blue color.





6- Using the 1 mL plastic pipette, add Thiosulfate Reagent drop by drop, swirling after each drop, while keeping an accurate count of the drops being added to the solution



- 7- Continue adding Thiosulfate Reagent until the solution changes from blue to colorless.
- 8- To obtain the concentration in ma/L (or ppm) of total chlorine in your sample, multiply by 10 the number of drops of Thiosulfate Reagent used to turn the solution from blue to colorless

drops x 10 = ma/L Total Chlorine

REFERENCES

Standard methods for the Examination of Water and Wastewater, 20th Ed., 1998, APHA-AWWA-WEF

HEALTH AND SAFETY

The chemicals contained in this kit may be hazardous if improperly handled. Read the relevant Health and Safety Data Sheet before performing this test.